

# Introduction

Name: ZL-1001 Low-frequency electromagnetic vibration test machine











Tel: +86-769-33657986 Fax: +86-769-33657987 Website: www.zltester.com E-mail: Zhongli@zltester.com



## 东莞中力仪器科技有限公司

#### ZhongLi Instrument Technology Co., Ltd.

### **Equipment summary:**

This machine is suitable for electronic, electro-mechanical, optical communications, packaging, auto parts, toys and other industry research, development, quality control and manufacturing. quality control inspection and production line, assembly line. It is more suitable for quality inspection of finished product for improving product quality.

#### **Main functions:**

Sine wave (half-wave / full wave), FM, sweep, programmable, frequency-doubling of the number, amplitude, maximum acceleration, time control, 485 Tong Xun interface, simple set acceleration, simple fixed amplitude

#### **Technical parameter:**

Model	ZL-1001
Vibration table size	50×1×50cm (L*H*W)
Table size	Vertical 50×20×50cm (L*H*W)
Vibration direction	Vertical
Max testing load	0∼100 (Kg)
FM function (1~400HZ)	either a frequency in the frequency range must be (maximum acceleration / 20g maximum amplitude / 5mm)
Sweep function (1~400HZ)	(up frequency / down frequency / time range) can be swept back and forth by setting arbitrarily standard
Programmable Function	1 ~ 15 of each segment can be arbitrarily set (frequency / time)
(1~400HZ)	can be recycled
Harmonic function (1∼400HZ)	1 ~ 15 multiply increase ① low to highfrequency ② high to low frequency ③low to high and then to low frequency / can be recycled
Logarithmic function (1~400HZ)	3 kinds of model number / can be recycled
Vibration Machine frequency(KW)	1.5
amplitude(mmp-p)	0∼5mm
Maximun Acceleration	0∼20g
Vibration wave	Sine wave (half-wave / full wave)
Time control	Can be installed at any time (seconds)
Supply voltage (V)	220±20%
Maximum current(A)	7

 Tel: <u>+86-769-33657986</u>
 Fax: +86-769-33657987

 Website: <u>www.zltester.com</u>
 E-mail: <u>Zhongli@zltester.com</u>



## 东莞中力仪器科技有限公司

# ZhongLi Instrument Technology Co., Ltd.

Full-featured computer-controlled	it need to buy a adapter if want to control, storage, recording and
(need to purchase)	print by computer.
Precision	Frequency can display to the 0.01Hz, precision 0.1Hz
Shows the acceleration amplitude	if you want to know the value of amplitude, acceleration,
(optional)	maximum acceleration, the exact figure need to purchase this measuring instrument

Note: 1g = 9.8 m/s 2 acceleration (unit g) =  $0.002 * f^2$  (frequency units HZ) \* D (amplitude units mmp-p)

 Tel: +86-769-33657986
 Fax: +86-769-33657987

 Website: www.zltester.com
 E-mail: Zhongli@zltester.com